



DRESTER DYNAMIC TRIPLE BY HEDSON

Convenient operation

The transfer of the solvents between the gun cleaner and the recycler is fully automated; the dirty, heavy and hazardous manual solvent handling is eliminated and at the same time the equipment and floor in the workshop sustains clean. Instantly after the transfer of solvents, access to clean solvent in the gun cleaner is available. The system allows for the units to be placed either close together or in separate rooms up to 25 meters (subject to local fire legislation). The convenient operation of the Drester Dynamic Triple by Hedson system encourages to run the system often. This keeps the solvent in the gun cleaner in better condition, resulting in improved gun cleaning performance. The consumption of solvent is reduced, the waste of solvent is kept to a minimum and costs are cut dramatically



COST SAVINGS

Reduce the solvent consumption to save money and the environment



TIME SAVING

Keep the spray guns cleaner and speed up the workflow



SAFE AND CLEAN

The dirty and hazardous manual solvent handling is eliminated and keeps the workshop clean

TECHNICAL SPECIFICATION

| | |
|----------------------------|--|
| Drester RXD - Docking unit | Part.no. RDX-8012 (Drester Classic 2600, 3600 & 8000) |
| Drester RXD - Docking unit | Part.no. RDX-9012 (Drester Boxer Aqua & Boxer Solvent) |
| Drester 120 - Recycler | Part.no. DR-120-A |

DRESTER RXD - DOCKING UNIT

| | |
|-----------------------|----------------------------|
| Weight | 21 kg (46 lbs) |
| Height | 700 mm (17,5") |
| Diameter | 500 mm (19,5") |
| Compressed air needed | Clean, dry air at 3-10 bar |
| Solvent capacity | Max. 80 liters |
| Pump capacity | 10 l/minutes |
| Liquid pressure | 2 bar |

DRESTER 120 - RECYCLER

| | |
|------------------------------|-----------------------------------|
| Weight | 67 kg (148 lbs) |
| Width | 590 mm (23") |
| Height | 1610 mm (63") |
| Max depth | 120 mm (47") |
| Type of solvents distillable | Thinner type |
| Boiler capacity | 12 litres |
| Residues discharge | Plastic bag |
| Condensation system | By air |
| Condensate material | Stainless steel |
| Time/cycle | 3-4 hours |
| Voltage | 200-240 V single Phase 50 or 60Hz |
| Electrical construction | Explosion proof |

CONSUMABLES

RECYCLE BAGS

Recycle bags for waste handling
Part.no. 11061